

## MP1700-MP1875E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

### Generator Output Rating at - 50Hz

380-415V	KVA	KW
Prime	1700.0	1360.0
Standby	1875.0	1500.0

@ 0.8 p.f.

### Generator Output Rating at - 60Hz

480V	KVA	KW
Prime	N/A	N/A
Standby	N/A	N/A

@ 0.8 p.f.

### Engine Data

Engine Manufacturer:	Perkins UK
Engine Model:	4012-46TAG3A
Number of Cylinders:	12
Cylinder Arrangement:	60 Vee
Cycle:	4 Stroke
Bore/Stroke mm (in):	160.0 (6.3) / 190.0 (7.5)
Induction:	Turbo charged & air - to- air Charge cooled
Compression ratio:	13.6:1
Displacement I (cu.in):	45.8 (2797.5)

### General Data

	Liter	US/Gal
Fuel Tank Capacity:	N/A	N/A
Fuel Tank:	N/A	
Base Frame:	Heavy Duty-Powder Coated	
Control Panel:	Deep Sea Electronics 6110	
Circuit Breaker:	ABB 3 Pole ACB	

\*Breaker supplied loose in a standalone cabinet on open type generating sets

### Performance

	50Hz		60Hz	
Engine Speed:	1500		1800	
Gross Engine Power:	<i>kWm</i>	<i>Bhp</i>	<i>kWm</i>	<i>Bhp</i>
Prime:	1500.0	2012.0	N/A	N/A
Standby:	1643.0	2203.0	N/A	N/A
Fuel Consumption:	<i>L/Hr</i>	<i>US Gal/Hr</i>	<i>L/Hr</i>	<i>US Gal/Hr</i>
Prime:	370	97.70	N/A	N/A
Standby:	405	107.0	N/A	N/A

### Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

### Dimensions and Weights

Length		Width		Height		Dry		Wet	
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
5300.0	208.7	2200.0	87.0	2680.0	105.6	10890	24008	11095	24460

\* With Lube Oil

\* With Lube Oil & Coolant

### Marapco Ltd

8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF  
Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com

**P Prime Rating**

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

**S Standby Rating**

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings*. The alternator model is peak continuous rated (as defined in ISO 8528-3)

**Air Flow****50 Hz****60 Hz**

	M <sup>3</sup> /min	Ft <sup>3</sup> /min	M <sup>3</sup> /min	Ft <sup>3</sup> /min
Combustion Air Flow:	135.0	4768	N/A	N/A
Exhaust Gas Flow:	350.0	12360	N/A	N/A
Radiator Cooling Air Flow:	2220.0	78399	N/A	N/A

\*Cooling system designed to operate in high ambient conditions

**Alternator Data**

**Alternator Manufacturer:** Leroy Somer

**Alternator Model:** LSA 51.2 S55

**Number of Bearings:** Single (1)

**Insulation Class:** H

**Total Harmonic Content:** 4.00%

**Wires:** 6

**Ingress Protection Rating:** IP 23

**Excitation System:** AREP

**Winding Pitch Code:** 2/3 - 6S

**Principles**

Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.

**Diesel Power**


Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	210.0	55.5	N/A	N/A
Lube Oil Capacity:	117.0	46.8	N/A	N/A

	°C	°F	°C	°F
Exhaust Temperature:	480	896	N/A	N/A

**Other Information****Generating Set Standards**

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

**Warranty**

This generator is covered against manufacturing and workmanship defects. Kindly refer to warranty statement for more details.

Picture shown in leaflet may include optional accessories

**Distributed & Serviced by:**