

MP2250-MP2500E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

General Data

Generator Output Rating at - 50Hz							
380-415V	KVA		KW				
Prime	2250		1800.0				
Standby	2500		2000.0				
			@ 0.8 p.f.				
Generator Ou	utput Rating	at - 60Hz					
480V	KVA		KW				
Prime	N/A		N/A				
Standby	N/A		N/A				
			@ 0.8 p.f.				
Engine Data							
Engine Manuf	facturer:	Perkins	s UK				
Engine Model	:	4016-61TRG3					
Number of Cy	linders:	16					
Cylinder Arrai	ngement:	60° Vee					
Cycle:	4 Str	stroke, compression ignition					
Bore/Stroke n	nm (in):	160 x 190					
Induction:		Turbo charged					
Compression	ratio:	13:1 nominal					
Displacement	I (cu.in):	61.12	23				

	Lite	r	US/	Gal		
Fuel Tank Capacity:	N/A	N/A		N/A		
Fuel Tank:		N/A				
Base Frame:	Heavy Dut	y-Powde	er Coate	d		
Control Panel: Deep Sea Electronics						
Circuit Breaker:	ABB	3 Pole A	СВ			
*Breaker supplied loose	in a standalone c	abinet on op	en type gene	rating sets		
Performance	5	0Hz	60	60Hz		
Engine Speed:	1500		1800			
Gross Engine Power	: kWm	Bhp	kWm	Bhp		
Prime:	1975.0	2648.5	N/A	N/A		
Standby:	2183.0	2927.4	N/A	N/A		
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr		
Prime:	470	124.1	N/A	N/A		
Standby:	529	139.7	N/A	N/A		

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights									
Length		Wid	Width Height		[Dry		Wet	
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
5803	228.4	2225	87.5	3930	154.7			15700	34612.5
		* With Lube Oil		* With Lube Oil	& Coolant				

Rating Definition



These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50	60	60 Hz		
	M ³ /min	Ft ^³ /min	M³/min	Ft³/min	
Combustion Air Flow:	160.0	5650	N/A	N/A	
Exhaust Gas Flow:	525.0	18540	N/A	N/A	
Radiator Cooling Air Flow:	3318.0	117174	N/A	N/A	

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data

Alternator Manufacturer:	Leroy Somer		
Alternator Model:	LSA 52.3 L9		
Number of Bearings:	Single (1)		
Insulation Class:	Н		
Total Harmonic Content:	< 3.5%		
Wires:	6		
Ingress Protection Rating:	IP 23		
Excitation System:	AREP		
Winding Pitch Code:	2/3 - n° 6S		

Principles



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Logos and Brands of Perkins, Leroy Somer, ABB & Deep Sea Electronics are Registered Trademarks

Cooling & Lubrication	;	50 Hz	(60 Hz		
	Liter	US/Gal	Liter	US/Gal		
Coolant Capacity:	270.0	71.3	N/A	N/A		
Lube Oil Capacity:	213.0	56.2	N/A	N/A		
	°C	°F	°C	°F		
Exhaust Temperature:	475	887	N/A	N/A		

Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warranty statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:

0802/2017