

LUBSOL (M) SDN. BHD. (546004-A)

Product Data Sheet



SANMOS DIZEL T3 Series (USA Formula)

Ultimate Heavy Duty Diesel Engine Oil

PRODUCT FEATURES

SANMOS DIZEL T3 Series is an ultimate, heavy-duty diesel engine lubricants designed and formulated for use in diesel engines used in trucks, fleets, mining, and earth moving equipment, construction, quarrying, agricultural industrial and farm equipment as well as for marine application.

APPLICATIONS

Suitable for use in a wide variety of heavy duty truck engines operating on highway including turbocharged engines and passenger car diesel engines, and off-highway equipment used in construction, mining and logging applications.

BENEFITS

- ♦ Multi-viscosity grade to suit most climatic conditions
- Excellent engine and piston ring belt cleanliness
- ♦ Superior engine wear protection performance
- Prevents build-up of carbon deposits, maintains oil consumption control and prevents ring sticking and bore polishing.

PERFORMANCE LEVELS

♦ API CI-4

TYPICAL SPECIFICATION



			SAE 15W-40	SAE 20W-50
PROPERTY	UNIT	TEST METHOD	SPECIFICATION	
Density at 15 deg C	kg/l	ASTM D 4052	0.8736	0.8832
Viscosity at 40 deg C	cSt	ASTM D 7042	110.94	157.25
Viscosity at 100 deg C	cSt	ASTM D 7042	14.50	17.50
Viscosity Index		ASTM D 2270	131	121
Flash Point COC	deg C	ASTM D 92	Min 220	Min 220
Pour Point	deg C	ASTM D 97	-24	-18
Total Base Number	mgKOH/g	ASTM D 2896	8.40	8.40

^{*} The above specifications are typical of current production, variation in these characteristics may occur, but will not affect the product performance.