LUBSOL (M) SDN. BHD. (546004-A)

Product Data Sheet

SANMOS DIZEL TX Series (USA Formula)

Ultimate Premium Heavy Duty Turbo Diesel Engine Oil

PRODUCT FEATURES

SANMOS DIZEL TX Series is an ultimate performance diesel engine oils that help increase engine life in the most severe on and off highway applications while delivering outstanding performance in modern, high-output, low-emission engines including those with Exhaust Gas Recirculation and Aftertreatment Filters and Diesel Oxidation Catalysts. Fully backwards compatible, SAE 15W-40 API CK-4 diesel engine oil will also deliver the same outstanding performance in older conventional engines.

APPLICATIONS

Specially recommended for the latest low-emissions, high performance diesel applications equipped with aftertreatment systems using Diesel Particulate Filter (DPF) and Diesel Oxidation Catalysts (DOC) technologies.

BENEFITS

- Superior soot-viscosity control.
- Outstanding thermal and oxidative stability.
- Excellent oil consumption control.
- Outstanding TBN reserves and stay-in-grade shear stability.
- Excellent low temperature pumpability.

PERFORMANCE LEVELS

♦ API CK-4

TYPICAL SPECIFICATION



			SAE 15W-40	SAE 20W-50
PROPERTY	UNIT	TEST METHOD	SPECIFICATION	
Density at 15 deg C	kg/l	ASTM D 4052	0.8732	0.8817
Viscosity at 40 deg C	cSt	ASTM D 7042	111.65	157.99
Viscosity at 100 deg C	cSt	ASTM D 7042	14.50	17.50
Viscosity Index		ASTM D 2270	133	121
Flash Point COC	deg C	ASTM D 92	Min 220	Min 220
Pour Point	deg C	ASTM D 97	-24	-18
Total Base Number	mgKOH/g	ASTM D 2896	11	11

* The above specifications are typical of current production, variation in these characteristics may occur, but will not affect the product performance.

62-1, Jalan Metro Perdana Barat 2, Taman Usahawan Kepong, 52100 Kuala Lumpur, Malaysia. Tel: (+603) 6250 6162 Fax: (+603) 6250 6172 E-mail: info@lubsol.com.my

An ISO 9001 Certified Company



